

AUDIO SYSTEM AND HEAD ATTACHMENT AUDIO UNIT

Background of the Invention

1. Technical Field

5 The present invention relates to an audio system for reproducing information recorded on a medium such as music or the like, in particular relates to an audio system suitable for portable purpose.

2. Description of the Related Art

10 This application claims benefit of priority under 35USC§119 to Japanese Patent Application No. HEI 11-152952, filed on May 31, 1999 the entire contents of which are incorporated by reference herein.

15 In general, a portable audio system, as shown in Figs. 1 and 2, with a small reproducing unit 103 or 104 mountable a memory medium such as a memory card 101 or a cassette tape 102, reads for instance music information recorded on a mounted memory medium. The read music information is transmitted from the reproducing unit 103 or 104 through a
20 connecting cord 105 to a headphone 106. Thereby, with the headphone 106, music can be heard.

Recently, as disclosed in Japanese Patent Application No. HEI 5-39167 (Japanese Patent Laid-open Application (KOKAI) No. HEI 6-251080), there is a wireless audio system.
25 That is, the wireless audio system reads music information or the like of a memory card mounted on a reproduction unit to generate audio signal. The audio signal is FM transmitted from the reproduction unit side to a headphone side.

Further, an audio system disclosed in Japanese Patent Application No. HEI 6-139244 (Japanese Patent Laid-open Application (KOKAI) No. HEI 8-9483) can download audio data to a memory module such as a memory card or the like disposed to a headphone. The respective operation buttons including a play button of audio data or a volume control button or the like are disposed to the headphone itself. Thus, an audio system is constituted of the headphone alone.

However, the aforementioned audio system has the following problems. That is, the audio system disclosed in Japanese Patent Application No. HEI 5-39167 transmits FM audio signal. Accordingly, a transmitter/receiver circuit becomes complicated which necessarily results in higher costs. Further, FM-transmission of the audio signal necessarily invites a deterioration of sound quality and, if there is a user using a similar audio system in the neighborhood, there may be problems with radio interference.

Further, since the audio system disclosed in Japanese Patent Application No. HEI 6-139244 is constituted of a single headphone, each operation button is also mounted on the headphone itself. Accordingly, in the audio system, a user, when hearing sound, namely when wearing a headphone on his or her head, can not see various kinds of operation buttons. As a result, there is a problem of a difficulty in executing various kinds of operations for instance such as volume control, play stop or the like. In addition, in the audio system of this type, being short of display function or the like, there is no way to easily check memory remains of

the memory card or the like and a file number showing an order of music or the like. Accordingly, there is also a problem of convenience.

5

Summary of the Invention

The present invention is carried out to overcome these problems. The object of the present invention is to provide an audio system that, with a simple configuration, can reproduce sound information or the like with high sound quality and reliability, and is high in convenience and excellent in operability.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
22

control unit is not an audio signal or the like but the control signal that controls the audio signal at the head attachment audio unit side. Accordingly, the sound quality of for instance music to be outputted does not deteriorate in a transmission line between the remote control unit and the head attachment audio unit to result in outputting sound of high quality from the head attachment audio unit.

Brief Description of the Drawings

Fig. 1 is a diagram schematically showing an existing audio system.

Fig. 2 is a diagram schematically showing another existing audio system different from the audio system of Fig. 1.

Fig. 3 is a diagram schematically showing an audio system involving a first embodiment of the present invention.

Fig. 4 is a block diagram showing the audio system of Fig. 3.

Fig. 5 is a perspective view showing a memory card mounted on a headphone of the audio system of Fig. 3.

Fig. 6 is a perspective view showing a support card that holds attachable and detachable the memory card of Fig. 5.

Fig. 7 is a diagram schematically showing an audio system involving a second embodiment of the present invention.

Fig. 8 is a block diagram showing the audio system of Fig. 7.

Fig. 9 is a perspective view showing a remote control

unit involving a third embodiment of the present invention.

Fig. 10 is a diagram for explaining a situation of transmission and reception of signal when the remote control unit of Fig. 9 is operated.

5 Fig. 11 is a flowchart for explaining a power saving function that the remote control unit of Fig. 9 possesses.

Fig. 12 is a perspective view showing a pendant type remote control unit into which a shape of the remote control unit of Fig. 9 is modified.

10 Fig. 13 is a plan view showing a wristwatch type remote control unit into which a shape of the remote control unit of Fig. 9 is modified.

Fig. 14 is a perspective view of a ring type remote control unit involving a fourth embodiment of the present invention.

15 Fig. 15 is a cross section showing a constitution of an antenna portion of a remote control unit involving a fifth embodiment of the present invention.

20 Fig. 16 is a diagram schematically showing an audio system involving a sixth embodiment of the present invention.

Description of Preferred Embodiments

25 In the following, modes of implementation of the present invention will be explained with reference to drawings.

Fig. 3 is a diagram schematically showing an audio system involving a first embodiment of the present invention, Fig. 4 being a block diagram thereof.

As shown in these figures, the audio system 1 is constituted of for instance a headphone 2 that is a head attachment audio unit mounted on user's head and a remote control unit 3 for remote controlling the headphone 2.

5 To the headphone 2, an infrared rays receiver 5, an external interface 7, a system controller 8, a voice decoder 9, a D/A converter/amplifier 10, and a headphone speaker 11 are disposed. The infrared rays receiver 5 receives infrared control signal 4 transmitted when the remote control unit 3 is operated. To the external interface 7, a memory card 6 such as smart media or the like thereon for instance music information is codified as a compressed file to record is mounted. The system controller 8 integrally controls each portion of the headphone 2. The voice decoder 9 decodes the music information or the like coded and recorded in the memory card 6 as audio signal. The D/A converter/amplifier 10 converts the decoded music information from digital signal to analog signal to amplify. The headphone speaker 11 outputs the audio signal that is converted to the analog signal to amplify as sound.

The remote control unit 3 is constituted of a plurality of operation buttons 12, a pulse modulator 13, and an infrared rays transmitter 14. The plurality of operation buttons 12 controls a reproduction function or the like of the music information recorded in the memory card 6 mounted on the headphone 2. The pulse modulator 13 pulse modulates due to for instance PPM (Pulse Position Modulation) method the signal generated according to a pushed button 12 when a

certain operation button 12 is pushed down. Then infrared rays transmitter 14 transmits the control signal 4 modulated due to the pulse modulator 13 and controlling the headphone 2 to the headphone 2 due to the infrared rays.

5 The memory card 6 capable of freely attachable to and detachable from the headphone 2, as shown in Fig. 5, is constituted of a printed wiring board 15, a planar external connection terminal 16, a semiconductor element (not shown in the figure). The planar external connection terminal 16 is
10 disposed on one surface of the printed wiring board 15. The semiconductor element is mounted on the other surface of the printed wiring board 15 and connected to the planar external connection terminal 16 and the like. The semiconductor
15 element that the memory card 6 has is a NAND type EEPROM that is a serial access-type memory element sequentially inputting/outputting all of read data or write data and commands to and from a common I/O pin. The memory card 6 is constituted by bonding the connection terminals of such
20 semiconductor element and printed wiring board 15 to connect, further by connecting due to interlayer connection the connection terminals of the printed wiring board 15 and the planar external connection terminal 16 through via-holes.

Next, a case where due to an audio system 1 constituted like this the music information recorded in a memory card 6
25 is actually outputted as sound will be explained.

When a user, through an operation button 12 of a remote control unit 3, demands reproduction of music information recorded in a memory card 6 mounted on a headphone 2, signal

is generated according to the content of the operation button 12. The generated signal is pulse-modulated by a pulse-modulator 13 due to PPM method or the like, infrared control signal being transmitted from an infrared transmitter 14.

5 When the control signal 4 is received by an infrared receiver 5 of the headphone 2, a system controller 8 notices reproduction demand of the music information recorded in the memory card 6 as a compressed file. Thereafter, the system controller 8 reads the music information coded and recorded
10 in the memory card 6 and further a voice decoder 9 decodes as audio signal. The decoded audio signal is converted into analog signal and amplified through a D/A converter/amplifier 10 and outputted as sound from a headphone speaker 11.

Thus, according to the audio system of the present
15 invention, the headphone 2 have a function of reproducing the music information stored in the memory card 6 mounted on the headphone 2 body and of outputting sound corresponding the music information. The remote control unit 3 transmits the control signal for controlling the reproduction function of
20 the headphone 2. That is, according to the audio system 1 of the present embodiment, the signal transmitted from the remote control unit 3 is not audio signal or the like but is the control signal 4 for controlling the audio signal at the headphone 2 side. Accordingly, without deteriorating the
25 quality of the sound outputted from the headphone 2 in a transmission path between the remote control unit 3 and the headphone 2, the sound of high quality can be outputted from the headphone 2.

Further, according to the present audio system 1, the signal transmitted from the remote control unit 3 is the infrared control signal obviously less of data amount compared with the audio signal transmitted over FM waves or the like. Accordingly, circuit configuration and component configuration as a system can be made simpler to result in a constitution of inexpensive audio system. Still further, due to easiness of coding of the control signal of less data amount as well as the transmission of the control signal due to the infrared rays of high directionality, different from the transmission due to the FM waves, the radio interference or the like can be prevented from occurring. Further, in the audio system 1 of the present embodiment, being constituted with a simple circuit configuration and component configuration as mentioned above, the remote control unit 3 can be not only formed in a smaller size but also freely formed in a shape easy to carry. In addition, the headphone 2 and the remote control unit 3, being wireless, become easy to handle, respectively.

Further, in the audio system 1 of the present embodiment, a medium storing the music information is a memory card of extremely small size and capable of freely attachable and detachable to and from the headphone 2. Accordingly, the desired sound information can be freely edited by use of for instance a personal computer or the like. In addition to this, the headphone 2 can be constituted in a compact size. The memory card 6, when treated by a personal computer, as shown in Fig. 6, can be treated by use of a

support card 17 or the like. That is, the support card 17 holds for the memory card 6 to expose the planar external connection terminal thereof and to be capable of freely attaching and detaching. A not shown concave portion is disposed so that a contour of the memory card 6 conforms thereto.

As mentioned above, in the audio system 1 of the present embodiment, the memory medium recording the music information or the like is the memory card 6 capable of freely attachable to and detachable from the headphone 2. However, the memory medium can be a solid memory directly disposed on the headphone 2 body.

Thus, according to the above embodiment, the remote control unit can transmit the control signal over the radio.

Thereby, the present audio system can be constituted so that due for instance to infrared rays or the like that can simplify the circuit and component configuration the control signal is transmitted. Thereby, the audio system can be constituted less expensive and the control signal can be easily codified to result in suppression of an occurrence of radio interference different from the transmission due to FM electromagnetic waves. In addition, since the present audio system can be constituted in the simpler circuit and component configuration, not only a smaller remote control unit can be realized but also the remote control unit can be formed in a shape easy to carry such as a wristwatch type or a brooch type. Further, in the present audio system, the head attachment audio unit and the remote control unit being

wireless, each individual unit can be easily handled.

Still further, according to the present embodiment, the memory portion can be a memory medium capable of freely attaching to and detaching from the head attachment audio unit.

That is, in the present audio system, the memory portion can be the memory medium capable of freely attaching to and detaching from the head attachment audio unit.

Accordingly, by employing for instance a memory card or the like as the memory medium, with a personal computer or the like desired sound information can be freely edited and the head attachment audio unit can be constituted in a compact size.

Further, in the present audio system, the memory portion can be a solid memory disposed on the head attachment audio unit body.

The present audio system can provide the head attachment audio unit with a solid memory as a memory portion wherein sound information is stored. Accordingly, in the solid memory, desired sound information can be recorded in advance.

Further, in the present audio system, the head attachment audio unit comprises an input terminal for inputting audio signal from the exterior.

The present audio system can be provided with an input terminal such as a jack for inputting audio signal. Accordingly, by connecting the head attachment audio unit to an external reproduction unit having a reproduction function

of the sound information through the input terminal, the head attachment audio unit can be used as a general use headphone.

Further, in the present audio system, the head attachment audio unit may comprise a response portion for returning response signal corresponding to the control signal to the remote control unit, the remote control unit being able to comprise further a reception portion for receiving the response signal.

The present audio system can notify the response signal from the head attachment audio unit corresponding to the control signal transmitted from the remote control unit to the remote control unit. Accordingly, a user who operated the remote control unit can confirm whether or not the control based on the operation content is implemented at the head attachment audio unit side.

Further, in the present audio system, the remote control unit may further comprise a display portion for visually displaying the information based on the response signal received at the reception portion.

In the present audio system, a user who operated the remote control unit can grasp whether the control according to a content of operation is implemented at the head attachment audio unit side or not due to the information based on the response signal visually displayed. Accordingly, mishandling of the remote control unit or the like can be prevented from occurring. In addition, the memory remains of the memory portion of the head attachment audio unit therein sound information is recorded or battery remains for driving

the head attachment audio unit can be obtained at the remote control unit side.

Further, in the present audio system, the remote control unit may further comprise a plurality of control buttons, a transmitter/receiver, and a display portion. The plurality of control buttons carries out the control involving the reproduction of the sound information. The transmitter/receiver transmits the control signal corresponding to a pushed down control button when any one of the control button is pushed down and receives the response signal corresponding to the control signal. The display portion visually displays the information based on the response signal received by the transmitter/receiver.

The present audio system, when an arbitrary control button of the remote control unit is pushed down and the control signal corresponding to the control involving the reproduction of the pushed down control button is transmitted, can visually display the information based on the response signal from the head attachment audio unit on the display portion disposed at the remote control unit. Accordingly, a user who operates the remote control unit can grasp a mode of control involving the reproduction of the sound information at the head attachment audio unit side such as for instance play, reverse, fast forward or stop. As a result, whether an intended control is assuredly implemented at the head attachment audio unit side or not can be confirmed.

Further, in the present audio system, the transmitter/receiver that the remote control unit possesses

may be disposed on the same face with that where the display portion or the control buttons are disposed.

According to the present audio system, when a user puts the head attachment audio unit on user's head and operates the remote control unit observing the display portion or the control buttons of the remote control unit, the transmitter/receiver is necessarily directed to the head attachment audio unit side that is put on the user's head. Accordingly, the user, without noticing a direction of the remote control unit, can assuredly implement transmission and reception of the control signal or the response signal to the control signal.

Further, in the present audio system, the remote control unit may further comprise an ON/OFF control portion for controlling ON/OFF of a main power source of the remote control unit body according to a situation of input from the control button.

According to the present audio system, ON/OFF control of the main power source of the remote control unit body is carried out according to a situation of input from the control button. For instance, when the control button is not pushed down for more than a prescribed period of time, the main power source of the remote control unit body is controlled to be OFF state. After the main power source becomes OFF, when the control button is pushed down, the main power source of the remote control unit body is controlled to be ON. Thereby, without damaging convenience as the system, power saving that is an important item for a portable

electrical appliance can be realized.

In the present audio system, the remote control unit comprises a transmitter for transmitting the control signal, and the transmitter may comprise an antenna for transmitting electromagnetic waves and a shield unit therein the antenna is inserted and having an opening at a prescribed position.

According to the audio system of the embodiment, even when the control signal is transmitted over electromagnetic waves, since the waves can be sent out of the opening, omnidirectional electromagnetic waves can be sent out only in a particular direction. Accordingly, the radio interference of the control signal can be prevented from occurring and other's head attachment audio unit is prevented from being wrongly operated in spite of the control of one's head attachment audio unit.

Further, audio signal or the like can be sent out of a memory portion disposed on the head attachment audio unit, being not necessary to be sent out of the remote control unit. Accordingly, even in the case of directionality being given in sending out the electromagnetic waves, during reproduction of the sound information such as during hearing music, the remote control unit is not required to incessantly direct toward the head attachment audio unit. Only when the head attachment audio unit is controlled, the remote control unit is necessary to be directed toward the head attachment audio unit. The user's load during handling the remote control unit can be alleviated accordingly.

In the audio system of the present embodiment, the

remote control unit may comprise a mechanism for attaching and detaching the remote control unit to and from a band of a wristwatch.

According to the audio system of the embodiment,
5 without wearing a band dedicated to a remote control unit on an arm, the remote control unit can be wore on an arm to carry. Accordingly, a convenience during carrying the remote control unit can be improved.

Further, in the audio system of the present embodiment,
10 the remote control unit can be a ring type.

According to the present audio system, the remote control unit, being able to fit on a finger, can be improved in the convenience thereof during carrying the remote control unit, and the remote control unit can be used as a kind of
15 fashion.

Further, in the audio system of the present embodiment,
the remote control unit can be a seal type.

According to the audio system of the present embodiment,
the remote control unit, being able to easily fit to various
20 places, can be improved in the convenience thereof during carrying the remote control unit.

Further, in the audio system of the present embodiment,
the remote control unit can be a wristwatch type.

According to the present audio system, a remote control
25 unit can be put on an arm. Accordingly, an inconvenience of carrying the remote control unit in a bag or a briefcase and of taking out the remote control unit of a bag or a briefcase can be avoided to result in an improvement of the convenience

during carrying the remote control unit.

Further, in the audio system of the present embodiment, the remote control unit can be a pendant type.

According to the audio system of the present embodiment,
5 the remote control unit, being able to carry by hanging from a neck, can eliminate trouble of bringing the remote control unit in a bag or a briefcase. Accordingly, the convenience during bringing the remote control unit can be improved.

Further, in the audio system of the present embodiment,
10 the remote control unit can be one body with a portable information terminal.

According to the audio system of the present embodiment, for instance, from a portable telephone and PHS, the head attachment audio unit can be controlled. Thereby, it is made
15 unnecessary to separately bring a remote control unit dedicated to the head attachment audio unit. Accordingly, load in carrying the remote control unit can be eliminated.

Further, in the audio system of the present embodiment, the sound information may be downloaded through a portable
20 information terminal to the memory portion.

According to the audio system of the present embodiment, for instance, from the portable telephone and the PHS, favorite music information can be stored in the memory portion at a desired time. Thereby, when desired, desired
25 music can be arbitrarily selected to hear.

Further, in the audio system of the present embodiment, the head attachment audio unit may comprise a mechanism for attaching and detaching the remote control unit.

According to the audio system of the present embodiment, during the remote control unit being unused, the remote control unit and the head attachment audio unit can be integrally handled. Accordingly, the remote control unit is prevented from being left behind and from being lost.

In the following, a second embodiment of the present invention will be explained with reference to the drawings. As shown in Figs. 7 and 8, in an audio system 21 of the present embodiment, to both of a headphone 22 and a remote control unit 23, a transmission function and reception function are disposed. That is, in the headphone 22 of the embodiment, in addition to the headphone 2 of the first embodiment, an infrared transmitter 25 for returning response signal 24 corresponding to control signal 4 received by an infrared receiver 5 to a remote control unit 23 is disposed.

Further, in the remote control unit 23 of the present embodiment, in addition to the constitution of the remote control unit 3 of the first embodiment, an infrared receiver 26 for receiving response signal 24 returned from the headphone 22, a liquid crystal display panel (LCD) 27 for visually displaying the information based on the response signal 24, and a LCD controller 28 for controlling the liquid crystal panel 27 are disposed. In addition, in the remote control unit 23, instead of the pulse modulator 13 of the remote control unit 3 of the first embodiment, a pulse modulator/demodulator 29 that pulse modulates the signal generated when the operation button 12 is pushed down and demodulates the response signal 24 received by the infrared

receiver 26 into electrical signal is disposed.

According to thus constituted audio system 21 of the present invention, the response signal 24 from the headphone 22 corresponding to the control signal 4 transmitted from the remote control unit 23 can be notified to the remote control unit 23. Thereby, a user who operated the remote control unit 23 can confirm whether the control based on the content of operation is implemented on the headphone 22 side or not due to the information based on the response signal 24 displayed on the liquid crystal display panel 27.

Accordingly, incorrect operation of the remote control unit 23 can be prevented from occurring. Further, according to the audio system 21 of the present embodiment, memory remains of the memory card 6 of the headphone 22 thereon music information is recorded or battery remains of the headphone 22 can be obtained at the remote control unit 23 side.

Further, to the headphone 22 of the present embodiment, a headphone jack may be disposed so that audio signal can be directly inputted from the external to a D/A

converter/amplifier 10. Due to disposition of such a headphone jack, an external reproduction unit capable of reproducing the music information can be connected with the headphone 22. Accordingly, the headphone 22 of the present embodiment can be used as an ordinary headphone.

Next, a third embodiment of the present invention will be explained. In the present embodiment, the remote control unit 23 of the second embodiment will be explained in detail. That is, the remote control unit 23, as shown in Fig. 9, is

constituted of a play button 31, a stop button 32, a reverse button 33, a fast forward button 34, a volume control button 35, an infrared transmitter/receiver 36, a liquid crystal display panel 27, and a data display button 37. The play
5 button 31 effects to play music information recorded in the memory card 6. The stop button 32 stops the play of the music information. The reverse button 33 rewinds a song to be played to a song of younger file No. The fast forward button 34 fast forwards a song to be played to a song of
10 older file No. The volume control button 35 controls the volume of the sound outputted from the headphone 22. The infrared transmitter/receiver 36 transmits the control signal 4 that controls an operation state of the headphone 22 and receives the response signal 24 returned from the headphone
15 22. The liquid crystal display panel 27 displays the information based on the response signal 24. The data display button 37 demands to display data at the headphone 22 side without influencing on a state of operation at the headphone 22 side.

20 The infrared transmitter/receiver 36 is disposed on a face of the remote control unit 23, that is, on the same face with that where the liquid crystal display panel 27, the play button 31 and the stop button 32 are disposed. That is, as shown in Fig. 10, a user 38, in operating the remote control
25 unit 23, operates it at a lower side of a front direction of the face of the user 38 where the liquid crystal display panel 27 of the remote control unit 23 can be most easily seen or the play button 31 and the stop button 32 can be

easily operated. Accordingly, the infrared transmitter/receiver 36 of the remote control unit 23 and the headphone 22 necessarily face to each other to result in a state of good communication of the control signal 4 or the response signal 24 that is infrared rays.

The data display button 37 sets to display real-time information at the headphone 22 side on the liquid crystal display panel 27 of the remote control unit 23 not so as to influence on mode in play at the headphone 22 side. For instance, during music play or the like, when, after the data display button 37 is pushed down, the stop button 32 is pushed down, the battery remains is displayed on the liquid crystal display panel 27. When, after the data display button 37 is pushed down, the fast forward button 34 is pushed down, the memory remains of the memory card 6 is displayed on the liquid crystal display panel 27. Other than these, as the real-time information to be displayed, file No showing in what order the music in play is, music name in play, repeat showing repetition of the same music, play period after the start of play, hold for nullifying input from a malfunction preventive button, or media mount display showing that the memory card 6 is mounted can be cited. In addition, when simply the play button 31, stop button 32, reverse button 33, or fast forward button 34 is pushed down, PLAY (reproduction), STOP (stoppage), REV (rewinding), or FF (fast forward) is displayed on the liquid crystal display panel 27, respectively.

Further, in the remote control unit 23 of the present

embodiment, all operation buttons play a role of power switch for turning ON a main power source. In addition, a power saving function for tuning automatically OFF the main power source when a definite period of time has elapsed after turning on any one of operation buttons is disposed. That is, as shown in Fig. 11, in the remote control unit 23, when, after key-entry from any one of operation buttons (S1), a definite period of time has elapsed without any key-entry from the operation button (S2), the main power source of the remote control unit 23 automatically turns OFF (S3). Further, after turning the power source OFF, when key-entered again from any one of operation buttons (S4), the main power source of the remote control unit 23 turns ON (S5).

Thus, according to the audio system of the present embodiment, when a certain operation button of the remote control unit 23 is pushed down and the control signal 4 responding the control involving the play of the pushed down button is transmitted, the information based on the response signal 24 from the headphone 22 can be visually displayed on the liquid crystal display panel 27 disposed to the remote control unit 23. Accordingly, a user 38 who operates the remote control unit 23 can grasp the control mode involving the play of the music information at the headphone 22 side such as for instance play, reverse, fast forward or stop. Accordingly, whether an intended control is assuredly implemented at the headphone 22 side or not can be confirmed. In addition, the memory remains of the memory card 6 therein the music information is stored, or the battery remains of

the headphone 22 side can be obtained at the remote control unit 23 side.

Further, in the audio system of the present embodiment, the infrared transmitter/receiver 36 is disposed on a surface of the remote control unit 23, that is on the same face with that where the liquid crystal display panel 27 or the PLAY button 31, STOP button 32 and the like are disposed. Thereby, when a user 38 wears the headphone 22 on her/his head and carries out an remote control operation through an operation button while observing the liquid crystal display panel 27 of the remote control unit 23, the infrared transmitter/receiver 36 is necessarily directed to the headphone 22 side.

Accordingly, according to the audio system of the present embodiment, a user 38, without noticing a direction of the remote control unit 23, can assuredly carry out transmission/reception of the control signal 4 or the response signal 24 responding to the control signal 4.

Further, according to the audio system of the present embodiment, according to the state of input from the operation button, ON/OFF control of the main power source of the remote control unit 23 is carried out. That is, when the operation button is not pushed down for more than a definite period of time, the main power source of the remote control unit 23 is controlled to be OFF. Further, when, after the main power source is turned OFF, the operation button is pushed down, the main power source of the remote control unit 23 is controlled to be ON. Accordingly, without damaging the convenience as the system, the saving of consumption power,

an important item for a portable electric appliance, can be realized.

The remote control units 3 and 23 of the present embodiments are operated in user's hand. However, as shown in Fig. 12 for instance, by downsizing the remote control units 3 and 23 as much as possible and attaching a chain 41 or the like, a pendant type remote control unit 42 can be constituted. Further, as shown in Fig. 13, by attaching a belt 43, a wristwatch type remote control unit 44 can be constituted. Other than these, the remote control unit can be constituted in for instance a brooch type or a key-ring type. Further, in order to further improve the convenience as the portable instrument, to the aforementioned remote control units of the present embodiments, watch function, game function, telephone function or pager function can be added to constitute an audio system.

Further, the remote control units 3 and 23 of the present embodiments may be provided with a mechanism for attaching and detaching the remote control unit 3 or 23 to and from a watchband. Here, as the mechanism for attaching and detaching the remote control unit 3 or 23 to and from the watchband, for instance, a clip or a rubber band can be attached to the remote control unit 3 or 23.

Thus, by disposing a mechanism for attaching and detaching the remote control unit 3 or 23 to and from the watchband, the remote control unit 3 or 23 can be brought with one's arm. Thereby, the convenience during bringing the remote control unit 3 or 23 can be improved.

Further, the headphone 2 or 22 of the present
embodiments may comprise a mechanism for attaching and
detaching the remote control unit 3 or 23. Here, as the
mechanism for attaching and detaching the remote control unit
5 3 or 23, for instance, a receiver capable of receiving the
remote control unit 3 or 23 can be disposed to the headphone
2 or 22.

Thus, due to disposition of the mechanism of attaching
and detaching the remote control unit 3 or 23 to and from the
10 headphone 2 or 22, the remote control unit 3 or 23 is
prevented from being lost to be incapable of controlling the
headphone 2 or 22.

Further, the remote control unit 3 or 23 of the present
embodiments may be a ring type remote control unit.

Fig. 14 is a perspective view showing a ring type
remote control unit involving a fourth embodiment of the
present invention. In Fig. 14, a remote control unit 51 is
provided with an operation button 52 and a ring 53 capable of
fitting to a finger. By wearing the remote control unit 51
15 thereto the ring 53 is disposed and by operating the
operation button 52, the headphone 2 or 22 can be operated.
Further, by adorning the remote control unit 51 or the ring
53, fashionability can be given.
20

Further, the remote control units 3 and 23 of the
present embodiments may be a seal type remote control unit.
Here, in order to stick the remote control unit as a seal, an
adhesive or a magic tape can be used.

Further, in the aforementioned embodiments, in order to

obtain directionality during transmitting/receiving the control signal 4 and the response signal 24, infrared rays are used. However, the control signal 4 and the response signal 24 can be transmitted/received through electromagnetic waves. In this case, in order to obtain directionality during transmitting/receiving the control signal 4 and the response signal 24, an antenna is preferably disposed in a shield unit having an opening at a prescribed position.

Fig. 15 is a cross section showing a constitution of an antenna portion of the remote control unit involving a fifth embodiment of the present invention. In Fig. 15, the shield unit 61 is provided with an opening 62, therein an antenna 63 being disposed. Electromagnetic waves 64 generated by the antenna 63 are sent out of the opening 62 outside the shield unit 61, electromagnetic waves in other direction than this being shielded by the shield unit 61. Accordingly, the electromagnetic waves 64 generated by the antenna 63 can be given directionality. Accordingly, even when the control signal 4 and the response signal 24 are transmitted/received over the electromagnetic waves 64, the control signal 4 and the response signal 24 can be prevented from being radio interfered.

Further, audio signal is sent out of the memory card 6 that is mounted on the headphone 2 or 22. Accordingly, even when the electromagnetic waves are sent out with directionality, only during operating the headphone 2 or 22, the remote control unit needs to be directed to the headphone 2 or 22. During music, the remote control unit is

unnecessary to be incessantly directed to the headphone 2 or 22. Accordingly, user's inconvenience during music with the headphone 2 or 22 can be alleviated.

Further, in the aforementioned embodiments, in order to
5 operate the headphone 2 or 22, the remote control unit 3 or 23 dedicated to an operation of the headphone 2 or 22 is used. However, the headphone 2 or 22 may be operated from a portable information terminal. Here, as the portable information terminal, a portable telephone and a PHS can be
10 employed.

Fig. 16 is a diagram schematically showing an audio system involving a sixth embodiment of the present invention. In Fig. 16, a portable telephone 75 is provided with an operation portion 76 for operating a headphone 71. Here,
15 when there is a piece of music that a user wants to hear, the music is selected by the portable telephone 75, transmission demand of the music being sent to the distributor of the music. Then, the distributor transmits the sound information demanded to transmit to the portable telephone 75. The
20 portable telephone 75, upon receiving (R1) the sound information transmitted from the distributor, downloads (R2) the received sound information to a memory card 74 mounted on a memory card socket portion that is not shown in the figure.

Next, upon downloading the sound information to the
25 memory card 74, the memory card 74 is taken out of the memory card socket portion of the portable telephone 75, being inserted (R3) in an external interface 72 disposed to the headphone 71.

Then, the user, when operating the headphone 71, operates an operation portion 76 of the portable telephone 75. Thereby, the control signal is transmitted from the portable telephone 75, the control signal being received (R4) by a receiver 73 disposed to the headphone 71. Thereby, the headphone 71, according to the control signal transmitted from the portable telephone 75, can play, fast forward, reverse or stop the sound information stored in the memory card 74.

Further, the headphone 71 may transmit the response signal showing a state of operation of the headphone 71 to the portable telephone 75. In this case, the portable telephone 75, upon receiving the response signal from the headphone 71, displays a state of operation of the headphone 71 shown by the response signal on a display portion 77 disposed to the portable telephone 75.

While the present invention has been particularly shown and described with reference to preferred embodiments thereof, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit, scope and teaching of the invention. Accordingly, the invention herein disclosed is to be considered merely as illustrative and limited in scope only as specified in the appended claims.